

HIGHLIGHTS

HIGHLIGHIS	
DEFIANT	 Trademark Can-Am DNA with next generation design Low seating position Ergo-Lok cockpit with four way adjustable seats
POWERFUL	 Industry leading 200 hp turbocharged and intercooled Rotax® ACE engine Advanced airflow dynamics QRS-X transmission
PRECISE	 TTX suspension with industry leading travel Ultra efficient and lightweight chassis Sharpest handling features
PLATFORM FEATURES	 72 in. (184.7 cm) wide 102 in. (259.1 cm) wheelbase 16 in. (40.6 cm) of ground clearance High torque Dynamic Power Steering (DPS™) Up to 24 in. (61 cm) suspension travel Rear tow hook
SPECIFIC TO X rc TURBO RR PACKAGE	 Belt monitoring system 850 W Magneto 200 hp Turbo RR engine Smart-Lok^{TM++} front differential FOX† 3.0 PODIUM RC2† shocks with bypass 15 in. (38.1 cm) aluminum beadlock wheels 32 in. (81.3 cm) Maxsis Liberty† tires Front bumper, half-doors, aluminum roof, intrusion bar Front tow hook HMWPE differential and under bumper skid plates HMWPE front and rear suspension arm UHMWPE rock sliders 4.500-lb (2,041kg) winch with synthetic rope 4-point harness with shoulder pads X-package graphics/seats 7.6 in. (19.3 cm) digital display with keypad Horn, Buzzer, Evap system Can-Am LED signature Painted color



Chalk Gray & Magma Red

DIMENSIONS / CAPACITIES

Estimated Dry Weight *	1,843 lb (836 kg)
Chassis / Cage	Dual-phase 980 steel
LxWxH	134.5 x 72.8 x 68.5 in. (341.6 x 184.9 x 174 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	16 in. (40.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Central console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)
Fuel Capacity	10.5 gal (40 L)
FEATURES	
Gauge	7.6 in. (19.3 cm) wide digital display with keypad: Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT / ECO [™] modes, seat belt and 4 x 4 indicator, front and rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature, DPS [™] mode
Instrumentation	Lighter type DC Outlet in central console
Magneto	850 W
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	4,500 lb (2,041 kg) winch with synthetic rope
Protection	Front bumper Half-doors Aluminum roof Intrusion bar 4-point harness with shoulder pads UHMWPE rock sliders HMWPE skidplates Full heavy duty with differential / Under bumper / Front and rear suspension arm Rear tow hook

WARRANTY

Factory warranty 2-year BF

2-year BRP limited warranty

Construction with the second s



ENGINE

Туре	149 kW (200 hp*), Rotax® ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler and high- performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L / H / N / R / P
Drive Train	Lockable front differential with exclusive Smart-Lok* technology. True 4 modes traction system: 2WD / 4WD with front diff. lock / 4WD ROCK / 4WD TRAIL *Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS™)

SUSPENSIONS

Front Suspension	Arched double A-arm with sway bar / 22 in. (55.9 cm) travel / Trophy truck inspired arms
Front Shocks	FOX† 2.5 PODIUM RC2† Piggyback with bypass, dual speed compression and rebound adjustments
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar and arched lower links / 24 in. (61 cm) travel
Rear Shocks	FOX† 3.0 PODIUM RC2† remote reservoir with bypass, dual speed compression and rebound adjustments

TIRES / WHEELS

TIRES / WITELES	
Front Tires	Maxxis Liberty† 32 x 10 x 15 in. (81.3 x 25.4 x 38.1 cm)
Rear Tires	Maxxis Liberty† 32 x 10 x 15 in. (81.3 x 25.4 x 38.1 cm)
Wheels	15 in. (38.1 cm) cast-aluminum beadlock

BRAKES

BRAKES	
Front	Dual 262 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm disc brakes with hydraulic twin-piston calipers
*149kw/200hp based on MY22 U.S. EPA certification, or 145kw/195hp based on current EU NRMM certification.	